Class 2

Building Product Information Sheet

About this form

This template has been developed to help manufacturers and importers into Aotearoa New Zealand provide the information required by the **Building (Building Product Information Requirements) Regulations 2022.**

How to use

- > Download and save this form in your computer.
- > Fill out the form with the relevant information about your product.
- > You may use this filled out form and publish it on your product web page.

Types of building products

There are two classes of designated building products with different information requirements for each. The below summarises the information that must be provided for each class of product and when the information must be made available.

Class 1: Batch or mass-produced products

Batch or mass-produced products that are typically available for retail or wholesale purchase. For example, cladding products, mechanical fixings, insulation products, internal lining, roofing products, structural wood-based products, structural steel and reinforcing products, sanitary plumbing, and drainage products, including tapware (note: this is not an exhaustive list).

Class 2: Custom-made lines of products

Custom-made lines of products that are made to order to client specifications. For example, external window joinery and doors that have been customised to the specifications of individual clients (for example, specifications on dimensions and glass type).

MBIE provides resources to support manufacturers, importers, wholesalers, distributors, and retailers to understand what their obligations are, and how to meet them.

For more information, visit Building product information requirements | Building Performance

Background

The Building Amendment Act 2021 introduced new minimum information requirements for building products to support better informed decision-making by building consent authorities, building owners, builders, and designers. The new regulations designate several building products for which building product information must be provided and establish the minimum requirements for that information.

The new regulations will ensure better and more consistent information is available for these products, helping inform building consent authority decisions on building consent applications. This should result in fewer requests for information, and therefore faster processing times. In addition, the requirements will ensure people, including homeowners, are given the information they need to make good decisions about products, and use and maintain them as intended.

Please note that The Ministry of Business, Innovation and Employment (MBIE) is not responsible for the input details provided in the template.

Class 2

Building Product Information Sheet

Troduce Harrie (menade	the brand name;		
Pacific Doors PSW120			
Product line (the produ	act line from which the product is	customised):	
Forster steel glazed fir	e windows		
Product description and its intended use (measurements, materials, usage):			
The Pacific Forster Pre	sto -/120/- is a fixed glazing, s	teel framed fire rated window.	It provides 120 minutes of integrity only.
The thickness of the window frame is 50 mm with an approximate glazed weight of 35 kg/m2			
Product identifier (if a	pplicable):		
	(6711)	. (00	
		response code (QR code), or any o 	ther distinguishable part/model number or identifier.)
Place of manufacture	: 🕢 Aotearoa New Zealand	Overseas	
Legal and trading nan	ne of the manufacturer(s):		
Pacific Door Systems L	td		
Address for service:			
STREET NAME 17 Meachen St. SUBURB Seaview		B Seaview	
CITY, COUNTRY Lower Hu	tt, New Zealand	POSTCO	DDE 5045
Website:	www.pacificdoors.co.nz		
Email address:	sales.pacificdoors@assaabloy.com		
Phone No. (if applicable):			
NZBN (if applicable):			

1

Address for service: Supplies Supplies Supplies	Legal and trading nam	e of the importer (if applicable):
Email address: Phone No. (if applicable):		
Website: Email address: Phone No. (If applicable): NZBN (If applicable): Relevant Building Code clauses: B2 Durability: Performance clause B2.3.1(b) C Protection from fire: Performance clauses C AS/2 4.2 and C5.1 Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. CAS/2 4.2 and C5.1: The PSW120 is tested in accordance with A51530.4:2014 and complies with NZ54232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: A3 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZ5 4232.2:1988"Performance Criteria for fire resisting closures - Fire resisting glazing systems"	Address for service:	
Website: Email address: Phone No. (if applicable): Relevant Building Code clauses: B2 Durability: Performance clause B2.3.1(b) C Protection from fire: Performance clauses C AS/2 4.2 and C5.1 Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZ54232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988" Performance Criteria for fire resisting closures - Fire resisting glazing systems"	STREET NAME	SUBURB
Email address: Phone No. (if applicable): NZBN (if applicable): Relevant Building Code clauses: B2 Durability: Performance clause B2.3.1(b) C Protection from fire: Performance clauses C AS/2 4.2 and C5.1 Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZS4232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988" Performance Criteria for fire resisting closures - Fire resisting glazing systems"	CITY, COUNTRY	POSTCODE
Phone No. (if applicable): Relevant Building Code clauses: B2 Durability: Performance clause B2.3.1(b) C Protection from fire: Performance clauses C AS/2 4.2 and C5.1 Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZS4232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988 "Performance Criteria for fire resisting closures - Fire resisting glazing systems"	Website:	
Relevant Building Code clauses: B2 Durability: Performance clause B2.3.1(b) C Protection from fire: Performance clauses C AS/2 4.2 and C5.1 Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZS4232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988 "Performance Criteria for fire resisting closures - Fire resisting glazing systems"	Email address:	
Relevant Building Code clauses: B2 Durability: Performance clause B2.3.1(b) C Protection from fire: Performance clauses C AS/2 4.2 and C5.1 Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZS4232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988 "Performance Criteria for fire resisting closures - Fire resisting glazing systems"	Phone No. (if applicable):	
B2 Durability: Performance clause B2.3.1(b) C Protection from fire: Performance clauses C AS/2 4.2 and C5.1 Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZ54232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988"Performance Criteria for fire resisting closures - Fire resisting glazing systems"	NZBN (if applicable):	
Statement on how the building product is expected to contribute to compliance: B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZ54232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988"Performance Criteria for fire resisting closures - Fire resisting glazing systems"	Relevant Building Cod	e clauses:
B2.3.1(b): The PSW120 can be finished to provide a durability of at least 15 years in all interior applications, excepting applications where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZS4232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988 "Performance Criteria for fire resisting closures - Fire resisting glazing systems"		
where the product is subjected to direct exposure to moisture. Durability is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. C AS/2 4.2 and C5.1: The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZS4232.2:1988. Compliance is dependent on product being installed and maintained in accordance with Pacific Door Systems Ltd requirements. Relevant standards: AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988"Performance Criteria for fire resisting closures - Fire resisting glazing systems"	Statement on how the	e building product is expected to contribute to compliance:
AS 1530.4:2014 "Methods for fire tests on building materials, components and structures. Part 4: Fire-resistance tests for elements of construction" NZS 4232.2:1988"Performance Criteria for fire resisting closures - Fire resisting glazing systems"	where the product is s in accordance with Pac C AS/2 4.2 and C5.1: The	ubjected to direct exposure to moisture. Durability is dependent on product being installed and maintained ific Door Systems Ltd requirements. The PSW120 is tested in accordance with AS1530.4:2014 and complies with NZS4232.2:1988. Compliance is
elements of construction" NZS 4232.2:1988"Performance Criteria for fire resisting closures - Fire resisting glazing systems"	Relevant standards:	
AS/NZS 4284:1995 "Testing of building facades"	NZS 4232.2:1988"Perfo	ormance Criteria for fire resisting closures - Fire resisting glazing systems"
	AS/NZS 4284:1995 "Te	sting of building facades"

 options for compliance set out in section 19 of the Act (regulations, acceptable solution, verification method) standard or technical document that describes the performance of the building product or the relevant specifications to which the building
 product was manufactured physical properties of the building product how the building product is intended to be used.
Limitations on the use of the building product:
The PSW120 is tested to AS/NZ4284 for water ingress in exterior applications. E2 compliance is dependent on suitable flashing system design by others.
If this product is installed in an exterior wall it should be given the maximum possible amount of protection, including overhead protection. Flashing design, supply, and installation by others.
Limitations on fire ratings, size and other product options are as per product datasheet.

_	nts that would support the use of the building product:
ne PSW120 is des indow is require	igned for use in interior or exterior residential and commercial buildings where a 120-minute single glazed i.
II specifications	are listed in the product datasheet: https://www.pacificdoors.co.nz/fire/forster-steel-glazed/windows/psw
	ements (also provide link to the product installation guide): uirements: https://www.pacificdoors.co.nz/fire/forster-steel-glazed/windows/psw120/installation
per product rec	unements. https://www.pacincuoors.co.nz/me/101ster-steer-glazed/windows/psw120/installation

Maintenance require	Maintenance requirements (also provide link to the product maintenance guide):		
As per Pacific Door Sy	stems Ltd Glazed Screens Operations and Maintenance manual:		
https://www.pacificdoors.co.nz/sites/default/files/images/Glazed%20Screens%20%20Handling%20and%20care%20manual%20%28End%20User%29.pdf			
Is the building produ	ct/building product line subject to warning or ban under section 26?:		
Yes ✓ No			
If yes, description of the warning or ban under section 26:			
Version:	01		
Date:	0 9 1 1 2 3		